PEUGEOT PARTNER TEPEE B9 PARTNER TEPEE 1.6I 16V VTI 5FS (2012-2016)



ENGINE EP6 Capacity: 4,25 liter, Filter capacity: 0,25 liter				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Avanza MSP 0W-30	Presteza MSP 5W-30	Avanza MSP+ 5W-30		

USE	efill) CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	
Check every 24 months/ 30000 km	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1081	

Capacity: 0-0 liter (Between min and max.)	Al HALTE
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Check every 30000 km, change every 24 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	

PEUGEOT PARTNER TEPEE B9 PARTNER TEPEE 1.6I 16V VTI 5FS (2012-2016)



ELECTRO-HYDRAULIC POWER STEER Capacity: 1,8 liter	ING (EHPS)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Check every 24 months/ 30000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Check every 20000 km/ 12 months		
HYDRAULIC POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
COOLING SYSTEM		
Capacity: 5,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 24 months/ 30000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Check every 20000 km/ 12 months