

PONTIAC (USA / CAN) AZTEK AZTEK 3.4 V6 (2001-2005)



MOTOR LA1
Kapacitet: 3,8 liter

ANVEND		KLIMA
Fleksibel (max)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Presteza MSP 5W-30	Xedoz FE 5W-30	

DIFFERENTIALE BAG (4x4)
Kapacitet: 1,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 12 måneder

GEAR AUTOMATISK 4/1

Kapacitet: 7 liter (2WD), Kapacitet: 8,3 liter (4WD), Kapacitet: 9,5-10,3 liter (Overhaling kapacitet)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 12 måneder, skift alle 100000 mil

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 12 måneder, skift alle 50000 mil

REDUKTIONSGEARKASSE

Kapacitet: 0,29 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 12 måneder

PONTIAC (USA / CAN) AZTEK AZTEK 3.4 V6 (2001-2005)



HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

SERVOSTYRING

Kapacitet: 0,75 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 2032		

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 12 måneder

KØLESYSTEM

Kapacitet: 9,1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 15	Coolant SP 15+	

Kontroller alle 12 måneder, skift alle 150000 mil/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.