

PORSCHE (EU) 911 993 911 CARRERA (1993-1995)



MOTOR M64.05/06

Kapacitet: 9 liter, Kapacitet: 11,5 liter (Førstegangsopfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

PRODUKTANBEFALING 3

Bi-Turbo 15W-40

Skift alle 20000 km/ 12 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Emperol 5W-40

PRODUKTANBEFALING 2

Emperol 5W-50

Skift alle 20000 km/ 12 måneder

DIFFERENTIALE FRA EN AUTOMATISK

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 20000 km/ 12 måneder, skift alle 80000 km

GEAR AUTOMATISK 4/1

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 20000 km/ 12 måneder, skift alle 40000 km

TRANSAKSEL MANUEL 6/1

Kapacitet: 3,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 20000 km/ 12 måneder, skift alle 80000 km

PORSCHE (EU) 911 993 911 CARRERA (1993-1995)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,34 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid Racing

Kontroller alle 20000 km, skift alle 24 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid Racing

Kontroller alle 20000 km, skift alle 24 måneder

SERVOSTYRING

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 20000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.