

PORSCHE (EU) 911 996 911 CARRERA (2002-2003)



MOTOR M 96/05

Kapacitet: 8,3 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Specialsynth MSP 5W-40	Helar 0W-40	Emperol 5W-40

Skift alle 20000 km/ 12 måneder

DIFFERENTIALE FRA EN AUTOMATISK

Kapacitet: 0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 20000 km/ 12 måneder, skift alle 160000 km

GEAR AUTOMATISK Tiptronic A96.10 / A96.35 5/1

Kapacitet: 9,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Kontroller alle 20000 km/ 12 måneder, skift alle 160000 km

TRANSAKSEL MANUEL G96.01 / G96.31 6/1

Kapacitet: 2,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 20000 km/ 12 måneder, skift alle 160000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,45 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid Racing		

Skift alle 24 måneder

PORSCHE (EU) 911 996 911 CARRERA (2002-2003)



HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid Racing

Kontroller alle 20000 km, skift alle 24 måneder

SERVOSTYRING

Kapacitet: 1,27 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 20000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 22,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.