

PORSCHE (EU) 911 997 911 CARRERA (2004-2008)

**ENGINE** M 96/05

Capacity: 8,25 liter, Filter capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Helar 0W-40	Emperol 5W-40

*Change every 30000 km/ 24 months***DIFFERENTIAL FROM AUTOMATIC**

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

*Change every 180000 km/ 120 months***TRANSAXLE MANUAL** G97.01 / G97.31 6/1

Capacity: 2,9 liter (Dry fill), Capacity: 2,6 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

*Change every 180000 km/ 120 months***TRANSMISSION AUTOMATIC** Tiptronic A97.01 / A97.31 5/1

Capacity: 9 liter (Dry fill), Capacity: 4,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

*Change every 180000 km/ 120 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 24 months/ 30000 km

PORSCHE (EU) 911 997 911 CARRERA (2004-2008)



POWER STEERING

Capacity: 1,27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 24 months/ 30000 km

COOLING SYSTEM

Capacity: 32 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.