

PORSCHE (EU) 944 944 S2 (1988-1991)**ENGINE**

Capacity: 6,5 liter, Capacity: 7,5 liter (Plastic sump)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

HDX 20W-50*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40*Change every 20000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 20000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Check every 20000 km/ 12 months, change every 80000 km/ 48 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 20000 km, change every 24 months*

PORSCHE (EU) 944 944 S2 (1988-1991)**POWER STEERING**

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 20000 km/ 12 months***COOLING SYSTEM**

Capacity: 7,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.