PRODUCT RECOMMENDATION

# PORSCHE (EU) BOXSTER 987 BOXSTER (2006-2009)

## ENGINE M 97/20
Capacity: 7,75 liter, Filter capacity: 0,25 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Specialsynth MSP 5W-40** | **Helar 0W-40** | **Emperol 5W-40** |

*Change every 30000 km/ 24 months*

## DIFFERENTIAL FROM AUTOMATIC
Capacity: 0,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Gear 1011** | **Syngear TDL 75W-90** | |

*Change every 180000 km/ 144 months*

## TRANSAXLE MANUAL G87.01 5/1
Capacity: 3,2 liter (Dry fill), Capacity: 2,25 liter (Service fill)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Gear 1011** | **Syngear TDL 75W-90** | |

*Change every 180000 km/ 144 months*

## TRANSAXLE MANUAL G87.20 6/1
Capacity: 2,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **SP Gear 1011** | **Syngear TDL 75W-90** | |

*Change every 180000 km/ 144 months*

## TRANSMISSION AUTOMATIC Tiptronic A87.01 / A87.02 5/1
Capacity: 9 liter (Dry fill), Capacity: 3,5 liter (Service fill)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **SP Matic 2032** | | |

*Change every 180000 km/ 144 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# PORSCHE (EU) BOXSTER 987 BOXSTER
(2006-2009)

## HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,4 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Drauliquid-LV Super DOT 4** | | |

*Change every 24 months*

## POWER STEERING
Capacity: 1 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **SP Fluid 3013** | | |

## COOLING SYSTEM
Capacity: 22 liter, Capacity: 22,4 liter (+ automatic transmission/transaxle)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Coolant SP 12** | **Coolant SP 12 EVO** | |

*Check every 24 months/ 30000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367