

PORSCHE (EU) PANAMERA 970

PANAMERA 4 (2013-2016)

**ENGINE** M46.20 / M46.40

Capacity: 9,8 liter (Dry fill), Capacity: 8,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Specialsynth MSP 5W-40	Helar 0W-40	Emperol 5W-40

*Change every 30000 km/ 24 months***DIFFERENTIAL FRONT**

Capacity: 0,53 liter (Dry fill), Capacity: 0,43 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR

Capacity: 1,1 liter (Dry fill), Capacity: 1 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 1,25 liter (Dry fill), Capacity: 1,15 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear LS 1015		

TRANSMISSION SEMI-AUTOMATIC C70.01 / C70.31 / ZF 7DT75 7/1

Capacity: 9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

PORSCHE (EU) PANAMERA 970

PANAMERA 4 (2013-2016)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 12 EVO	

PORSCHE DYNAMIC CHASSIS CONTROL (PDCC)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.