

RENAULT (EU) 21 B48 / K48 21 1.7 TS, GTS, RS, TSE (1986-1993)



MOTOR F2N-C

Kapacitet: 5,2 liter, Filterkapacitet: 0,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Emperol 5W-50	Asyntho 5W-30

Skift alle 10000 km/ 12 måneder

TRANSAXSEL MANUEL JB3 5/1

Kapacitet: 3,4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Kontroller alle 10000 km, skift alle 50000 km

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1		
SP Gear 1081		

Kontroller alle 10000 km, skift alle 50000 km

HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0,7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 50000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 1,1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

RENAULT (EU) 21 B48 / K48 21 1.7 TS, GTS, RS, TSE (1986-1993)



KØLESYSTEM

Kapacitet: 6,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 50000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.