

RENAULT (EU) 21 B48 / K48 21 TURBO DIESEL (1986-1995)



MOTOR J8S-B714

Kapacitet: 5,3 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Asyntho 5W-30	Emperol 10W-40	Bi-Turbo 15W-40

Skift alle 7500 km

TRANSAKSEL MANUEL NG9 5/1

Kapacitet: 2,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Kontroller alle 7500 km, skift alle 60000 km

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
SP Gear 1081		

Kontroller alle 7500 km, skift alle 60000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 60000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

RENAULT (EU) 21 B48 / K48 21 TURBO DIESEL (1986-1995)



KØLESYSTEM

Kapacitet: 7,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 60000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.