

RENAULT (EU) 9 X42 9 1.1 (1981-1989)



MOTOR C1E

Kapacitet: 3,25 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

PRODUKTANBEFALING 2

HDX 20W-50

Skift alle 10000 km/ 12 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Skift alle 10000 km/ 12 måneder

TRANSAKSEL MANUEL 4/1

Kapacitet: 3,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 10000 km/ 12 måneder, skift alle 50000 km/ 36 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 10000 km/ 12 måneder, skift alle 50000 km/ 36 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 3,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 10000 km/ 12 måneder, skift alle 50000 km/ 36 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 10000 km/ 12 måneder, skift alle 50000 km/ 36 måneder

RENAULT (EU) 9 X42 9 1.1 (1981-1989)



HYDRAULISK BREMSESYSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 50000 km/ 36 måneder

KØLESYSTEM

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 50000 km/ 36 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.