

RENAULT (EU) ESPACE II J63 ESPACE II 2.85 V6I J63 (1993-1996)



MOTOR Z7W713

Kapacitet: 7 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

PRODUKTANBEFALING 2

Emperol 5W-50

PRODUKTANBEFALING 3

Asyntho 5W-30

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

DIFFERENTIALE FRA EN AUTOMATISK AR4

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 10000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 10000 km, skift alle 50000 km

GEAR AUTOMATISK AR4 4/1

Kapacitet: 4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 10000 km, skift alle 50000 km

TRANSAKSEL MANUEL UN1 5/1

Kapacitet: 3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 20000 km, skift alle 50000 km

RENAULT (EU) ESPACE II J63 ESPACE II 2.85 V6I J63 (1993-1996)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 10000 km/ 12 måneder, skift alle 40000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 10000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.