

RENAULT (EU) LAGUNA B56 / K56 LAGUNA 3.0 V6 B56 / K56 (1993-1997)



MOTOR Z7X

Kapacitet: 7 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Emperol 5W-50	Asyntho 5W-30

Kontroller alle 1000 km, skift alle 10000 km/ 12 måneder

DIFFERENTIALE FRA EN AUTOMATISK AD8

Kapacitet: 1,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Skift alle 60000 km/ 36 måneder

GEAR AUTOMATISK AD8 4/1

Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Skift alle 60000 km/ 36 måneder

TRANSAKSEL MANUEL PK1 015/017/030/032 5/1

Kapacitet: 2,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 10000 km/ 12 måneder

TRANSAKSEL MANUEL PK1 046/047 5/1

Kapacitet: 2,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 10000 km/ 12 måneder

RENAULT (EU) LAGUNA B56 / K56 LAGUNA 3.0 V6 B56 / K56 (1993-1997)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 1000 km, skift alle 60000 km/ 36 måneder

HYDRAULISK BREMSESYSTEM ABS

Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

Kontroller alle 1000 km, skift alle 60000 km/ 36 måneder

SERVOSTYRING

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 10000 km

KØLESYSTEM

Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Kontroller alle 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.