

RENAULT (EU) SUPER 5 B40 / C40 / S40 5 GTL (1985-1988)



MOTOR C1J

Kapacitet: 3,5 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Emperol 5W-50	Asyntho 5W-30

Skift alle 10000 km/ 12 måneder

TRANSAKSEL MANUEL JB4 4/1

Kapacitet: 2,75 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 10000 km, skift alle 50000 km

TRANSAKSEL MANUEL JB5 5/1

Kapacitet: 2,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 10000 km, skift alle 50000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 50000 km

KØLESYSTEM

Kapacitet: 5,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Skift alle 50000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUKTANBEFALING

RENAULT (EU) SUPER 5 B40 / C40 / S40 5 GTL (1985-1988)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.