

# RENAULT (EU) TWINGO II C44 TWINGO II

## 1.2 16V (2007-2014)

**ENGINE D4F**

Capacity: 4 liter, Filter capacity: 0,2 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Duranza LSP 5W-30</b> | <b>Meganza MSP 5W-30</b> | <b>Avanza RPC 5W-30</b>  |

*Change every 30000 km/ 12 months*

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Severe                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Duranza LSP 5W-30</b> | <b>Meganza MSP 5W-30</b> | <b>Avanza RPC 5W-30</b>  |

*Change every 15000 km/ 6 months***TRANSAXLE MANUAL JB1 5/1**

Capacity: 3,1-3,4 liter

| USE                      |                            | CLIMATE  |
|--------------------------|----------------------------|----------|
| Normal                   |                            | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   |          |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> |          |

*Check every 12 months/ 30000 km***TRANSAXLE SEMI-AUTOMATIC JH1 5/1**

Capacity: 2,8 liter

| USE                      |                            | CLIMATE  |
|--------------------------|----------------------------|----------|
| Normal                   |                            | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   |          |
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> |          |

*Check every 12 months/ 30000 km***HYDRAULIC GEARBOX ACTUATION SYSTEM**

Capacity: 0,6 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

# RENAULT (EU) TWINGO II C44 TWINGO II

## 1.2 16V (2007-2014)



### HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

#### PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

### COOLING SYSTEM

Capacity: 5,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

#### PRODUCT RECOMMENDATION 1

**Coolant SP 16**

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*