RENAULT (EU) 9 X42 9 1.4 (50 KW) AUTOMATIC (1981-1989)



		1
Asyntho 5W-30	Emperol 10W-40	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Arctic
USE		CLIMATE
Change every 10000 km/ 12 months		
Bi-Turbo 15W-40	HDX 20W-50	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
ENGINE C1J Capacity: 3,25 liter (Service fill)		

Change every 10000 km/ 12 months

TRANSAXLE AUTOMATIC 3/1 Capacity: 4 liter (Dry fill), Capacity: 3 liter (Service fill)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
ATF Dexron II-D				
Change every 60000 km				

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3			

Change every 50000 km/ 36 months

COOLING SYSTEM Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 50000 km/ 36 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.