

# RENAULT (EU) CLIO III X85 CLIO III 1.2 16V 75 ETHANOL (2008-2013)

**ENGINE D4F-742**

Capacity: 4 liter, Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Meganza MSP 5W-30</b>	<b>Avanza RPC 5W-30</b>

*Change every 30000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Duranza LSP 5W-30</b>	<b>Meganza MSP 5W-30</b>	<b>Avanza RPC 5W-30</b>

*Change every 15000 km/ 6 months***TRANSAXLE MANUAL JH3 5/1**

Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>SP Gear 5015</b>	<b>Gearlube RPC 75W-80</b>

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Drauliquid-LV Super DOT 4</b>	

*Check every 30000 km/ 12 months, change every 120000 km/ 48 months***COOLING SYSTEM**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Coolant SP 16</b>	

*Check every 30000 km/ 12 months, change every 120000 km/ 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.