RENAULT (EU) CLIO III X85 CLIO III 2.0 16V (2006-2007)

ENGINE M4R
Capacity: 4,4 liter (Dry fill), Capacity: 3,5 liter (Service fill), Filter capacity: 0,2 liter

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Duranza LSP 5W-30	**Helar 0W-40**	**Emperol 5W-40**	

Change every 30000 km/ 12 months

USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Duranza LSP 5W-30	**Helar 0W-40**	**Emperol 5W-40**	

Change every 15000 km/ 6 months

TRANSAXLE AUTOMATIC DP0 4/1

USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
SP Matic 2032	**ATF Almirol**	

TRANSAXLE MANUAL TL4 6/1
Capacity: 2 liter

USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

RENAULT (EU) CLIO III X85 CLIO III 2.0 16V (2006-2007)

COOLING SYSTEM
Capacity: 5,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 16

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.