

# RENAULT (EU) DUSTER H79 DUSTER 1.6

## 16V BI-FUEL (2010 AND AFTER)



**ENGINE** K4M LPG  
Capacity: 4,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Helar MSP+ 5W-40</b>	<b>Specialsynth MSP 5W-40</b>	<b>Helar 0W-40</b>

*Change every 30000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Helar MSP+ 5W-40</b>	<b>Specialsynth MSP 5W-40</b>	<b>Helar 0W-40</b>

*Change every 15000 km/ 6 months*

**TRANSAXLE MANUAL** JR5 5/1  
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>Gearlube RPC 75W-80</b>	

### HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid-LV Super DOT 4</b>		

*Check every 15000 km/ 12 months, change every 90000 km/ 48 months*

### POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

# RENAULT (EU) DUSTER H79 DUSTER 1.6 16V BI-FUEL (2010 AND AFTER)



## COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 16</b>		

*Check every 15000 km/ 12 months, change every 90000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*