
RENAULT (EU) KANGOO K76 KANGOO 1.2





ENGINE D7F Capacity: 3,7 liter, Filter capacity: 0,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza LSP 5W-30	Helar 0W-40	Emperol 5W-40

Change every 20000 km/ 12 months

TRANSAXLE MANUAL JB1 5/1 Capacity: 3,4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Gearlube RPC 75W-80		
Check every 48 months/ 60000 km			

HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 60000 km/ 36 months	,	

POWER STEERING Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 20000 km/ 12 months	·

COOLING SYSTEM Capacity: 5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 16	
Change every 120000 km/ 48 months	<u> </u>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

information contained herein is subject to changes without notification.

RENAULT (EU) KANGOO K76 KANGOO 1.2 (1997-2000)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the