

RENAULT (EU) LATITUDE L43 LATITUDE 2.0 DCI (110 KW) (2010-2015)

**ENGINE M9R**

Capacity: 7,4 liter, Filter capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Helar 0W-40

Change every 30000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar MSP+ 5W-40	Specialsynth MSP 5W-40	Helar 0W-40

*Change every 15000 km/ 6 months***TRANSAXLE AUTOMATIC AJ0 6/1**

Capacity: 7,6 liter (Dry fill), Capacity: 3,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

TRANSAXLE MANUAL PK4 6/1

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

HYDRAULIC BRAKE SYSTEM ABS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

RENAULT (EU) LATITUDE L43 LATITUDE 2.0 DCI (110 KW) (2010-2015)

**COOLING SYSTEM**

Capacity: 7,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.