RENAULT (EU) LOGAN X90 LOGAN 1.2 16V X90 (2004 AND AFTER)



ENGINE D4F Capacity: 4 liter		
use Normal		climate Moderate
Presteza MSP 0W-30	Duranza LSP 5W-30	Helar 0W-40
Check every 15000 km/ 12 months, c	hange every 30000 km/ 24 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-30	Duranza LSP 5W-30	Helar 0W-40
Change every 15000 km/ 6 months		

TRANSAXLE MANUAL JH3 5/1 Capacity: 2,8 liter			
use Normal		сымате Moderate	
			PRODUCT RECOMMENDATION 1
SP Gear 5015	Gearlube RPC 75W-80		

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Check every 15000 km/ 12 months, change every 90000 km/ 48 months				

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

PRODUCT RECOMMENDATION

RENAULT (EU) LOGAN X90 LOGAN 1.2 16V X90 (2004 AND AFTER)



COOLING SYSTEM Capacity: 4,5 liter, Capacity: 5,5 liter (+ airconditioning)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 16				
Check every 15000 km/ 12 months, change every 90000 km/ 48 months				

Check every 15000 km/ 12 months, change every 90000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.