

# RENAULT (EU) SCÉNIC II J84 SCÉNIC II 1.9

## DCI DPF J84 (2005-2007)



**ENGINE** F9Q Common Rail  
Capacity: 4,9 liter, Filter capacity: 0,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3  |
|-----------------------------|-----------------------------|---------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> |

*Change every 15000 km/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3  |
|-----------------------------|-----------------------------|---------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> |

*Change every 7500 km/ 6 months*

**TRANSAXLE AUTOMATIC** DP0 4/1  
Capacity: 6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |  |

**TRANSAXLE MANUAL** ND0 6/1  
Capacity: 2,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2   |  |
|--------------------------|----------------------------|--|
| <b>SP Gear 5015</b>      | <b>Gearlube RPC 75W-80</b> |  |

**HYDRAULIC BRAKE SYSTEM ABS**  
Capacity: 1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         |  |  |
|----------------------------------|--|--|
| <b>Drauliquid-LV Super DOT 4</b> |  |  |

*Check every 15000 km/ 12 months, change every 120000 km/ 48 months*

# RENAULT (EU) SCÉNIC II J84 SCÉNIC II 1.9 DCI DPF J84 (2005-2007)

**COOLING SYSTEM**

Capacity: 7,6 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| Coolant SP 16            |  |          |

---

*Check every 15000 km/ 12 months, change every 120000 km/ 48 months*

---

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*