

RENAULT (EU) SCÉNIC III J95 SCÉNIC III 1.5 DCI 110 (2009-2016)



ENGINE K9K
Capacity: 4,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Helar MSP+ 5W-40

PRODUCT RECOMMENDATION 2

Specialsynth MSP 5W-40

PRODUCT RECOMMENDATION 3

Helar 0W-40

Change every 30000 km/ 12 months

TRANSAXLE MANUAL JR5 5/1
Capacity: 2,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

TRANSAXLE MANUAL TL4 6/1
Capacity: 1,9 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

TRANSAXLE SEMI-AUTOMATIC DC4 6/1
Capacity: 1,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072

HYDRAULIC BRAKE SYSTEM ABS
Capacity: 0-0 liter (Between min and max.)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

RENAULT (EU) SCÉNIC III J95 SCÉNIC III 1.5 DCI 110 (2009-2016)



COOLING SYSTEM

Capacity: 6,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 16

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

AIRCONDITIONING

Capacity: 480 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR

Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.