RENAULT (EU) TWINGO C06 TWINGO 1.2 LPG (1997-2007)



ENGINE D7F LPG Capacity: 4 liter, Filter capacity: 0,2 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Duranza LSP 5W-30	Helar 0W-40	Emperol 5W-40		
Change every 30000 km/ 12 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Duranza LSP 5W-30	Helar 0W-40	Emperol 5W-40		
Change every 15000 km/ 6 months				

TRANSAXLE MANUAL JB1 5/1 Capacity: 3,1 liter				
use Normal		сымате Moderate		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 5015	Gearlube RPC 75W-80			

HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 30000 km/ 12 months, ch	ange every 120000 km/ 48 months	

COOLING SYSTEM Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		
Chack avery 20000 km/12 months	hanga ayany 120000 km/ 12 mantha	

Check every 30000 km/12 months, change every 120000 km/48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.