

**ROVER 800 825I, STERLING (1986-1988)**

**ENGINE C25A**  
Capacity: 4,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Bi-Turbo 15W-40</b>	<b>Bi-Turbo 20W-50</b>	

*Change every 10000 km/ 6 months*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>	

*Change every 10000 km/ 6 months*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Emperol 5W-40</b>		

*Change every 10000 km/ 6 months*

**TRANSAXLE AUTOMATIC 4/1**  
Capacity: 3,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 20000 km, change every 40000 km/ 24 months*

**TRANSAXLE MANUAL 5/1**  
Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>	

*Check every 20000 km, change every 40000 km/ 24 months*

**ROVER 800 825I, STERLING (1986-1988)****HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 40000 km/ 48 months*

**POWER STEERING**

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 10000 km/ 6 months*

**COOLING SYSTEM**

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Change every 80000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*