

SAAB 9-3 CABRIOLET 9-3 CABRIOLET 2.0T (129 KW) (2003-2011)



MOTOR B207L

Kapacitet: 6,75 liter (Førstegangsupfyldning), Kapacitet: 6 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Helar MSP+ 5W-40	Specialsynth MSP 5W-40

Skift alle 30000 km/ 12 måneder

TRANSAKSEL AUTOMATISK FA 57 5/1

Kapacitet: 7,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Kontroller alle 30000 km/ 24 måneder, skift alle 120000 km/ 96 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 12 måneder/ 30000 km

TRANSAKSEL MANUEL F40 6/1

Kapacitet: 2,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 12 måneder/ 30000 km

HYDRAULISK TAGSYSTEM

Kapacitet: 0,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3013		

SAAB 9-3 CABRIOLET 9-3 CABRIOLET 2.0T (129 KW) (2003-2011)



HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 0,37 liter (Højrestyring), Kapacitet: 0,43 liter (Venstrestyring)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 30000 km/ 12 måneder, skift alle 48 måneder

SERVOSTYRING

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 7,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 12 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.