SAAB 9-5 9-5 2.0TID (140 KW) (2010-2011)



ENGINE Capacity: 4,5 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Helar 0W-40	
Change avery 20000 km/ 12 months	

Change every 30000 km/ 12 months

TRANSAXLE MANUAL F40-6 6/1 Capacity: 2,4 liter (Dry fill), Capacity: 2,2 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90	

Check every 12 months/ 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM A Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	

Check every 30000 km/ 12 months, change every 48 months

POWER STEERING Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Check every 12 months/ 30000 km	

COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Oh	· · · · · · · · · · · · · · · · · · ·	· · · ·

Check every 12 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

SAAB 9-5 9-5 2.0TID (140 KW) (2010-2011)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.