

**SAAB 900 900 TURBO (1979-1985)****ENGINE B201 Turbo**

Capacity: 4,3 liter (Dry fill), Capacity: 3,8 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Asyntho 5W-30</b>	<b>Emperol 10W-40</b>	

*Check every 3000 km, change every 10000 km/ 12 months***DIFFERENTIAL FROM AUTOMATIC**

Capacity: 1,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1081</b>	<b>SP Gear 5015</b>	

*Check every 20000 km/ 12 months***TRANSAXLE MANUAL 4/1**

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1081</b>	<b>SP Gear 5015</b>	

*Check every 20000 km/ 12 months***TRANSAXLE MANUAL 5/1**

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1081</b>	<b>SP Gear 5015</b>	

*Check every 20000 km/ 12 months***TRANSMISSION AUTOMATIC Borg Warner 37 3/1**

Capacity: 3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>ATF-F (Ford)</b>		

*Change every 40000 km/ 48 months*

**SAAB 900 900 TURBO (1979-1985)****HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 0,58 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 40000 km/ 48 months***POWER STEERING**

Capacity: 0,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**COOLING SYSTEM**

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Change every 36 months***AIRCONDITIONING COMPRESSOR** Sankyo SD508/SeikoSeiki SS170

Capacity: 170-175 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM**

Capacity: 0,95-1,15 kg

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*