

SAAB 9000 9000I 16 (1986-1990)**ENGINE B202i**

Capacity: 4,2 liter, Filter capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

*Change every 20000 km/ 12 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 8,4 liter (Dry fill), Capacity: 3,3-3,5 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

*Change every 40000 km/ 48 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

*Check every 20000 km/ 12 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 40000 km/ 48 months***POWER STEERING**

Capacity: 0,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

SAAB 9000 9000I 16 (1986-1990)**COOLING SYSTEM**

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.