

SAMSUNG SM5 L43 SM5 2.5 V6 (2011-2018)

ENGINE V4U
Capacity: 4,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 2

Meganza MSP 5W-30

PRODUCT RECOMMENDATION 3

Avanza RPC 5W-30

Change every 20000 km/ 12 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Duranza LSP 5W-30

PRODUCT RECOMMENDATION 2

Meganza MSP 5W-30

PRODUCT RECOMMENDATION 3

Avanza RPC 5W-30

Change every 10000 km/ 6 months

TRANSAXLE AUTOMATIC AJ0 6/1
Capacity: 7,6 liter (Dry fill), Capacity: 3,5 liter (Service fill)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

HYDRAULIC BRAKE SYSTEM ABS

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

POWER STEERING

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 12 months/ 30000 km

SAMSUNG SM5 L43 SM5 2.5 V6 (2011-2018)**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		

Check every 30000 km/ 12 months, change every 120000 km/ 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.