

SEAT (EU) ALHAMBRA 71, 711 ALHAMBRA 2.0 TDI (103 KW) 4DRIVE (2010-2015)



ENGINE CFFB
Capacity: 4,3 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30

Change every 15000 km/ 12 months

BEVEL GEAR TRANSFERBOX
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

DIFFERENTIAL REAR
Capacity: 0,95 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

TRANSAXLE MANUAL 0A6 6/1
Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015

Check every 24 months/ 30000 km

SEAT (EU) ALHAMBRA 71, 711 ALHAMBRA 2.0 TDI (103 KW) 4DRIVE (2010-2015)

**TRANSAXLE SEMI-AUTOMATIC DSG 02E (DQ250) 6/1**

Capacity: 6,9-7,2 liter (Initial fill), Capacity: 3-4 liter (Mechatronic Only), Capacity: 5,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072*Change every 60000 km***HALDEX-CLUTCH AS OF PRODUCTION DATE 30-10-2013**

Capacity: 0,75 liter (Initial fill), Capacity: 0,65 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 6036*Change every 36 months***HALDEX-CLUTCH UP TO PRODUCTION DATE 30-10-2013**

Capacity: 0,85 liter (Initial fill), Capacity: 0,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 6033*Change every 36 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 36 months*

USE	CLIMATE
Subsequently	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

SEAT (EU) ALHAMBRA 71, 711 ALHAMBRA 2.0 TDI (103 KW) 4DRIVE (2010-2015)

**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.