Change every 15000 km/ 12 months

Helar 0W-40

SEAT (EU) ALTEA XL 5P5 ALTEA XL 1.8 TSI (2007-2010)



ENGINE BYT, BZB Capacity: 4,6 liter		
use Extended drain (max)		climate Moderate
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 30000 km/ 24 months		·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 15000 km/ 12 months	,	·
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

TRANSAXLE MANUAL 02S 6/1 Capacity: 2,1 liter (Dry fill), Capacity: 1,9 liter (Service fill)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
SP Gear 1081	SP Gear 5015				
Check every 48 months/ 60000 km	1				

Emperol 5W-40

HYDRAULIC BRAKE/CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	·

Asyntho 5W-30

SEAT (EU) ALTEA XL 5P5 ALTEA XL 1.8 TSI (2007-2010)



COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Coolant SP 12	Coolant SP 12 EVO				
Check every 48 months/ 60000 km	•				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.