## **SEAT (EU) LEÓN 5F LEÓN 1.4 TSI (110 KW)** (2014-2017)



<b>ENGINE</b> CZDA, CZEA Capacity: 4 liter				
USE		CLIMATE		
Extended drain (max)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30			
Change every 30000 km/24 months				
USE		CLIMATE		

Normal

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 02S 6/1 Capacity: 2,3 liter (Dry fill), Capacity: 2,1 liter (Service fill)				
use Normal		climate Moderate		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1081	SP Gear 5015			

TRANSAXLE SEMI-AUTOMATIC 0CW 7/1 Capacity: 1,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1081	SP Gear 5015		

HYDRAULIC ACTUATION GEARBOX Capacity: 0,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

PRODUCT RECOMMENDATION

## **SEAT (EU) LEÓN 5F LEÓN 1.4 TSI (110 KW)** (2014-2017)



HYDRAULIC BRAKE/CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid-LV Super DOT 4				
Change every 24 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid-LV Super DOT 4				
Change every 36 months				
COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Moderate

Normal

PRODUCT RECOMMENDATION 1
Coolant SP 12 EVO

Check every 48 months/ 60000 km