SKODA FAVORIT FAVORIT 136 (1989-1994)



ENGINE Capacity: 3,3-4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Emperol 10W-40	Bi-Turbo 15W-40	

Change every 10000 km/6 months

TRANSAXLE MANUAL 5/1 Capacity: 2,4 liter				
use Normal		CLIMATE		
		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071		

Check every 10000 km/12 months, change every 40000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0,6 liter			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Change every 24 months	·		

COOLING SYSTEM Capacity: 6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	·

IGNITION DISTRIBUTOR

We are unable to give a standard recommendation for this component. Please contact our service department.

SKODA FAVORIT FAVORIT 136 (1989-1994)



STEERING BOX Capacity: 0,13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.