

# SKODA OCTAVIA I 1U OCTAVIA I 1.9 TDI (66 KW) 4X4 (2000-2006)



## ENGINE AGR

Capacity: 4,5 liter

| USE                  | CLIMATE  |
|----------------------|----------|
| Extended drain (max) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |  |
|-----------------------------|-----------------------------|--|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |  |

Change every 50000 km/ 24 months

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3      |
|-----------------------------|---------------------------|-------------------------------|
| <b>Helar SP LL-03 5W-30</b> | <b>Presteza MSP 5W-30</b> | <b>Specialsynth MSP 5W-40</b> |

Change every 15000 km/ 12 months

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Emperol 5W-40</b>     |  |  |

Change every 15000 km/ 12 months

## DIFFERENTIAL REAR

Capacity: 1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Syngear 75W-90</b>    |

Check every 30000 km

## TRANSAXLE MANUAL 02C 5/1

Capacity: 2,4 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>SP Gear 1081</b>      | <b>SP Gear 5015</b>      |  |

Check every 12 months/ 30000 km

# SKODA OCTAVIA I 1U OCTAVIA I 1.9 TDI (66 KW) 4X4 (2000-2006)



## HALDEX-CLUTCH

Capacity: 0,25 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 6033***Check every 30000 km*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 24 months*

## POWER STEERING

Capacity: 1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3013***Check every 60000 km*

## COOLING SYSTEM

Capacity: 6,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 12**

PRODUCT RECOMMENDATION 2

**Coolant SP 12 EVO***Change every 36 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.