Change every 30000 km/24 months

## SKODA RAPID NA "IND" RAPID 1.6 16V

(2011-2022)



ENGINE CLSA Capacity: 3,6 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30		
Change every 15000 km/ 12 months				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30			

TRANSAXLE AUTOMATIC 09G 6/1 Capacity: 7 liter (Dry fill), Capacity: 3 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4026				
Change every 60000 km		,		

TRANSAXLE MANUAL 02T 5/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 15000 km/ 12 months	'	'

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 1-1,15 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Check every 15000 km/12 months, change every 30000 km/24 months

PRODUCT RECOMMENDATION

## SKODA RAPID NA "IND" RAPID 1.6 16V

(2011-2022)



COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Check every 15000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.