

SKODA SUPERB II 3T SUPERB II 1.8 TSI (112 KW) 4X4 (2009-2013)



MOTOR CDAB
Kapacitet: 4,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Helar SP LL-03 5W-30

PRODUKTANBEFALING 2
Emperol 5W-40

PRODUKTANBEFALING 3
Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

ANVEND
Fleksibel (max)

KLIMA
Moderat

PRODUKTANBEFALING 1
Helar SP LL-03 0W-30

PRODUKTANBEFALING 2
Helar SP LL-03 5W-30

Skift alle 30000 km/ 24 måneder

DIFFERENTIALE BAG
Kapacitet: 0,93 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1011

PRODUKTANBEFALING 2
Syngear TDL 75W-90

KONISK TANDHJULSDREV
Kapacitet: 0,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1011

PRODUKTANBEFALING 2
Syngear TDL 75W-90

TRANSAKSEL MANUEL 02Q 6/1
Kapacitet: 2,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1081

PRODUKTANBEFALING 2
SP Gear 5015

Kontroller alle 15000 km/ 12 måneder

SKODA SUPERB II 3T SUPERB II 1.8 TSI (112 KW) 4X4 (2009-2013)



HALDEX-KOBLING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 6033

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Kontroller alle 15000 km/ 12 måneder, skift alle 24 måneder

SERVOSTYRING

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 8,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 48 måneder/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.