

SKODA SUPERB II 3T SUPERB II 2.0 TSI (2010-2013)



ENGINE CCZA
Capacity: 4,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Change every 15000 km/ 12 months

USE
Flexible (max)

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30

Change every 30000 km/ 24 months

TRANSAXLE SEMI-AUTOMATIC DSG 02E (DQ250) 6/1
Capacity: 7,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072

Change every 60000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Check every 15000 km/ 12 months, change every 24 months

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 15000 km/ 12 months

SKODA SUPERB II 3T SUPERB II 2.0 TSI (2010-2013)

**COOLING SYSTEM**

Capacity: 8,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 48 months/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.