Change every 30000 km/24 months

SKODA SUPERB III 3V SUPERB III 1.4 TSI (110 KW) 4X4 (2015-2019)



ENGINE CZDA, CZEA Capacity: 4,5 liter (Dry fill), Capacity	v: 4 liter (Service fill)	
USE		CLIMATE
Preferred, flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar FE LL-04 0W-20		
Change every 30000 km/ 24 month	s	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
Change every 15000 km/ 12 month	s	
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

ANGLE GEARBOX Capacity: 0,9 liter			
use Normal		сымате Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

DIFFERENTIAL REAR Capacity: 0,93 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

Change every 36 months

SKODA SUPERB III 3V SUPERB III 1.4 TSI (110 KW) 4X4 (2015-2019)



TRANSAXLE MANUAL 0BB 6/1 Capacity: 2,15-2,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 24 months/ 30000 km		

HALDEX-CLUTCH
Capacity: 0,74 liter (Dry fill), Capacity: 0,66 liter (Service fill)

USE

Normal

PRODUCT RECOMMENDATION 1

SP Fluid 6036

CLIMATE

Moderate

HYDRAULIC BRAKE SYSTEM
Capacity: 1,15 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Change every 24 months

CLIMATE
Moderate

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.