

SKODA SUPERB III 3V SUPERB III 1.4 TSI (92 KW) (2015-2019)

**ENGINE CZCA**

Capacity: 4,5 liter (Dry fill), Capacity: 4 liter (Service fill)

USE	CLIMATE
Preferred, flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar FE LL-04 0W-20*Change every 30000 km/ 24 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Asyntho 5W-30*Check every 15000 km/ 12 months*

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30*Check every 24 months/ 30000 km***TRANSAXLE MANUAL 0AJ 6/1**

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015*Check every 24 months/ 30000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

Capacity: 1,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

SKODA SUPERB III 3V SUPERB III 1.4 TSI (92 KW) (2015-2019)

**COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.