

SKODA SUPERB III 3V SUPERB III 2.0 TDI (140 KW) (2015-2020)

**ENGINE** DDAA, DFCA, DFHA

Capacity: 5,3 liter (Dry fill), Capacity: 4,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30

Change every 15000 km/ 12 months

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30

*Change every 30000 km/ 24 months***TRANSAXLE MANUAL** 02Q 6/1

Capacity: 2,15-2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1081	SP Gear 5015

*Check every 48 months/ 60000 km***TRANSAXLE SEMI-AUTOMATIC** DSG 0D9 6/1

Capacity: 6,9-7 liter (Dry fill), Capacity: 5,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 2072	

*Change every 60000 km***TRANSAXLE SEMI-AUTOMATIC** DSG 0GC 7/1

Capacity: 6,7-6,9 liter (Dry fill), Capacity: 6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 2072	

Change every 120000 km

SKODA SUPERB III 3V SUPERB III 2.0 TDI (140 KW) (2015-2020)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 1-1,15 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

COOLING SYSTEM AS OF PRODUCTION DATE 08-07-2019

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

COOLING SYSTEM UP TO PRODUCTION DATE 08-07-2019

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.