## **SKODA YETI 5L YETI 1.4 TSI (110 KW)** (2015-2017)



ENGINE CZDA Capacity: 4,3 liter (Dry fill), Capacity: 3,9 liter (Service fill)					
USE		CLIMATE			
Extended drain (max)		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30				
Change every 30000 km/24 months					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Holor OW/ 40	Emporal 5W/ 40	Acutha 5W/ 20			

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 Helar 0W-40
 Emperol 5W-40
 Asyntho 5W-30

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 0A4 5/1 Capacity: 1,8-2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Charle avenu 18 months/ 60000 km		

Check every 48 months/ 60000 km

HYDRAULIC BRAKE SYSTEM Capacity: 1-1,15 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	

Check every 30000 km/ 24 months, change every 24 months

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant SP 12 EVO				
Check even 24 menthe/ 20000 km				

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.