

SKODA YETI 5L YETI 1.8 TSI (118 KW) 4X4 (2012-2018)



MOTOR CDAA

Kapacitet: 4,6 liter (Servicepåfyldning), Kapacitet: 5,6 liter (Tør efterfyld)

ANVEND	KLIMA
Forlænget interval (max)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Skift alle 30000 km/ 24 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 0,93 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 24 måneder/ 30000 km

KONISK TANDHJULSDREV

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 24 måneder/ 30000 km

TRANSAKSEL MANUEL 02Q 6/1

Kapacitet: 2,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1081	SP Gear 5015	

Kontroller alle 24 måneder/ 30000 km

SKODA YETI 5L YETI 1.8 TSI (118 KW) 4X4 (2012-2018)



HALDEX-KOBLING

Kapacitet: 0,72-0,76 liter (Servicepåfyldning), Kapacitet: 0,78-0,85 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 6036

Skift alle 36 måneder

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Kontroller alle 30000 km/ 24 måneder, skift alle 24 måneder

KØLESYSTEM

Kapacitet: 8,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.