

SSANGYONG KORANDO C KORANDO C 2.0 2WD (2012-2014)



MOTOR G20DF
Kapacitet: 4,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Duranza ECO 5W-20

PRODUKTANBEFALING 2
Helar SP LL-03 5W-30

PRODUKTANBEFALING 3
Presteza MSP 5W-30

Skift alle 20000 km/ 12 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
Duranza ECO 5W-20

PRODUKTANBEFALING 2
Helar SP LL-03 5W-30

PRODUKTANBEFALING 3
Presteza MSP 5W-30

Skift alle 10000 km/ 6 måneder

TRANSAKSEL MANUEL 6/1
Kapacitet: 1,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

PRODUKTANBEFALING 2
Syngear 75W-90

Kontroller alle 60000 km/ 36 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

PRODUKTANBEFALING 2
Syngear 75W-90

Skift alle 120000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Filterkapacitet: 0-0 liter (Imellem min. og max.)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Skift alle 24 måneder

SSANGYONG KORANDO C KORANDO C 2.0 2WD (2012-2014)



SERVOSTYRING

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 20000 km/ 12 måneder

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 20000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Skift alle 200000 km/ 60 måneder

KLIMAANLÆGSSYSTEM

Kapacitet: 400-460 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.