

# SSANGYONG REXTON REXTON 290 TD

## (2002-2006)



**ENGINE** D29ST/ OM 662  
Capacity: 8-9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 5W-40</b>	<b>Emperol 5W-50</b>	<b>Asyntho 5W-30</b>

*Check every 3000 km, change every 10000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 5W-40</b>	<b>Emperol 5W-50</b>	<b>Asyntho 5W-30</b>

*Change every 5000 km/ 3 months*

**DIFFERENTIAL FRONT**  
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

*Check every 10000 km/ 12 months, change every 38000 km*

**DIFFERENTIAL REAR**  
Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

*Check every 10000 km/ 12 months, change every 38000 km*

**TRANSFERBOX (4x4)**  
Capacity: 1,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Check every 10000 km/ 12 months, change every 60000 km*

# SSANGYONG REXTON REXTON 290 TD

## (2002-2006)



### TRANSMISSION AUTOMATIC BTRA M74LE 4/1

Capacity: 9,5 liter (Overhaul capacity), Capacity: 3,4-3,6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

Check every 12 months/ 30000 km

### TRANSMISSION MANUAL T5WC M/T 5/1

Capacity: 3,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Almirol**

PRODUCT RECOMMENDATION 3

**ATF Dexron II-D**

Check every 50000 km

### HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

Check every 10000 km/ 12 months, change every 40000 km/ 24 months

### HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

Check every 10000 km/ 12 months, change every 40000 km/ 24 months

### POWER STEERING

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

Check every 10000 km/ 12 months

# SSANGYONG REXTON REXTON 290 TD

## (2002-2006)



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 3000 km, change every 10000 km/ 12 months*

### COOLING SYSTEM

Capacity: 10,5-11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Check every 10000 km/ 12 months, change every 36 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*