

SSANGYONG RODIUS / STAVIC RODIUS / STAVIC 270 XDI (2005-2009)

**ENGINE D27DT**

Capacity: 8,3 liter, Filter capacity: 2 liter

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Emperol 5W-50	Asyntho 5W-30

*Change every 10000 km/ 6 months***DIFFERENTIAL FRONT (4x4)**

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

*Change every 30000 km***DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

*Change every 30000 km***TRANSFERBOX (4x4)**

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 15000 km/ 12 months, change every 60000 km

SSANGYONG RODIUS / STAVIC RODIUS / STAVIC 270 XDI (2005-2009)

**TRANSMISSION AUTOMATIC 5/2**

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 15000 km/ 12 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

*Check every 15000 km/ 12 months, change every 60000 km***TRANSMISSION MANUAL 5/1**

Capacity: 3,6 liter, Capacity: 3,4 liter (2WD)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

*Check every 15000 km/ 12 months, change every 60000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 24 months***POWER STEERING**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 15000 km/ 12 months

SSANGYONG RODIUS / STAVIC RODIUS / STAVIC 270 XDI (2005-2009)


COOLING SYSTEM

Capacity: 11,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Change every 60000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.