

SUBARU (EU) LEGACY / OUTBACK BD, BG, BK LEGACY / OUTBACK 2.0 TURBO 4WD (1994-1996)



MOTOR EJ20 turbo
Kapacitet: 4,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Skift alle 12500 km/ 6 måneder

DIFFERENTIALE BAG (4x4)
Kapacitet: 0,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube RPC 75W-80

Kontroller alle 25000 km/ 12 måneder, skift alle 50000 km/ 24 måneder

DIFFERENTIALE FRA EN AUTOMATISK
Kapacitet: 1,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 25000 km/ 12 måneder, skift alle 50000 km/ 24 måneder

GEAR AUTOMATISK/REDUKTIONSGEARKASSE 4/1
Kapacitet: 8,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 25000 km/ 12 måneder, skift alle 50000 km/ 24 måneder

SUBARU (EU) LEGACY / OUTBACK BD, BG, BK LEGACY / OUTBACK 2.0 TURBO 4WD (1994-1996)



TRANSAKSEL MANUEL/REDUKTIONSGEARKASSE 5/1

Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		

Kontroller alle 25000 km/ 12 måneder, skift alle 50000 km/ 24 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	SP Gear 5015	Gearlube RPC 75W-80

Kontroller alle 25000 km/ 12 måneder, skift alle 50000 km/ 24 måneder

HYDRAULISK BREMSESYSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 50000 km/ 24 måneder

SERVOSTYRING

Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

KØLESYSTEM

Kapacitet: 7,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Skift alle 50000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.