

# SUBARU (EU) LEGACY / OUTBACK BD, BG, BK LEGACY / OUTBACK 2.0 (1994-1999)



**MOTOR EJ20**  
Kapacitet: 4 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Asyntho 5W-30**

PRODUKTANBEFALING 2

**Emperol 10W-40**

*Skift alle 12500 km/ 12 måneder*

**DIFFERENTIALE FRA EN AUTOMATISK**  
Kapacitet: 1,2 liter

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

*Skift alle 50000 km/ 24 måneder*

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**SP Gear 1011**

PRODUKTANBEFALING 2

**SP Gear 5015**

PRODUKTANBEFALING 3

**Gearlube RPC 75W-80**

*Skift alle 50000 km/ 24 måneder*

**GEAR AUTOMATISK 4/1**  
Kapacitet: 7,9 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**SP Matic 2032**

PRODUKTANBEFALING 2

**ATF Almirol**

PRODUKTANBEFALING 3

**ATF Dexron II-D**

*Skift alle 50000 km/ 24 måneder*

# SUBARU (EU) LEGACY / OUTBACK BD, BG, BK LEGACY / OUTBACK 2.0 (1994-1999)



## TRANSAKSEL MANUEL 5/1

Kapacitet: 3,3 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

*Skift alle 50000 km/ 24 måneder*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Gear 1011**

PRODUKTANBEFALING 2

**SP Gear 5015**

PRODUKTANBEFALING 3

**Gearlube RPC 75W-80**

*Skift alle 50000 km/ 24 måneder*

## HYDRAULISK BREMSESYSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

PRODUKTANBEFALING 3

**Drauliquid DOT 3**

*Skift alle 50000 km/ 24 måneder*

## SERVOSTYRING

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Matic 2032**

PRODUKTANBEFALING 2

**ATF Almirol**

PRODUKTANBEFALING 3

**ATF Dexron II-D**

*Kontroller alle 25000 km/ 12 måneder*

## KØLESYSTEM

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

*Skift alle 50000 km/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.