

SUBARU (EU) IMPREZA GE, GH IMPREZA 2.0 D (2008-2012)

**ENGINE**

Capacity: 7,2 liter (Dry fill), Capacity: 5,9 liter (Service fill), Filter capacity: 0,4 liter

USE

Preferred

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Duranza MSP 0W-30****PRODUCT RECOMMENDATION 2****Presteza MSP 0W-30****PRODUCT RECOMMENDATION 3****Helar SP LL-03 0W-30***Change every 15000 km/ 12 months***USE**

Alternative (acceptable)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar SP LL-03 5W-30****PRODUCT RECOMMENDATION 2****Presteza MSP 5W-30****PRODUCT RECOMMENDATION 3****Avanza MSP+ 5W-30***Change every 15000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,8 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Check every 30000 km/ 24 months, change every 60000 km/ 48 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****SP Gear 5015****PRODUCT RECOMMENDATION 3****Gearlube RPC 75W-80***Check every 30000 km/ 24 months, change every 60000 km/ 48 months***TRANSAXLE MANUAL/TRANSFERBOX 6/1**

Capacity: 3,7 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Check every 30000 km/ 24 months, change every 60000 km/ 48 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****SP Gear 5015****PRODUCT RECOMMENDATION 3****Gearlube RPC 75W-80***Check every 30000 km/ 24 months, change every 60000 km/ 48 months*

SUBARU (EU) IMPREZA GE, GH IMPREZA 2.0 D (2008-2012)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

COOLING SYSTEM

Capacity: 8,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 120000 km/ 72 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km/ 24 months, change every 220000 km/ 132 months

AIRCONDITIONING COMPRESSOR R-134a

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM R-134a

Capacity: 450-550 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.